

Construction: Solid Wooden Flooring

Product Details	
Product ID	100B50
Construction	Solid
Species (Top Layer)	Oak
Backing	_____
Joint type	Tongue and Groove
Edges	Not Beveled
Pattern	Brick



Packaging	Pack
Quantity	30
Coverage	1.05m2
Weight	12.6kg
H x W x L	500x70x16 mm

Dimensions	
Thickness	16 mm
Width	70 mm
Length	500 mm
Tongue Width	5 mm
Groove Width	5 mm

Deviations	
Deviation on thickness	± 1 mm
Deviation on width	± 1 mm
Cup	≤ 0.4 % of plank width
Bow	≤ 0.7 % of length
Spring	≤ 0.7 % of length
Height Difference	≤ 0.4 % of length

Installation




Glue down over concrete, plywood or wooden subfloor. Suitable for gluedown installation over radiant heating systems.

General Specifications

Use	Residential, light commercial or commercial (Polyurethane Commercial)
Accessory	- Round Stair nosings, Scotias, Skirting, Corners and Transition profiles - Polyurethane glue
Guarantee	Relative humidity must always be maintained

Storage & Usage



Air humidity 40% – 65%
Temperature +18 ° – +22 ° C

Grade: Natural

Description	
Surface Grade	Natural
Plywood Grade	_____
Smooth Tight	Unlimited
Holes	Not Allowed
Bark Pockets	Allowed Width 40mmx3mm 3 Pieces, No Cracking, Must be Filled.
Color Variation	Not Worst Natural Color Variation
Sound Knots	No Limited, Could be crack knots.
Dead Knots	Dead Knot Allow $\varphi < 30\text{mm}$, Must be Filled.
Pin Knots	Allow 3 -5 pcs per board
Ring Shake	Not Allowed
Ends Crack	Closed Crack Length 50mm Allowed.
Surface Crack	Not Allowed

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specifcation at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.