

Construction: 2-layer T&G Engineered Flooring

| Product Details     |                         |
|---------------------|-------------------------|
| Product ID          | 100K120                 |
| Construction        | Eng. Multi-Ply          |
| Species (Top Layer) | Oak                     |
| Backing             | Baltic Birch Wood       |
| Joint type          | Loose tongue and groove |
| Edges               | 4-sided bevel (4V)      |
| Pattern             | Brick                   |



| Packaging | Pack               |
|-----------|--------------------|
| Quantity  | 20                 |
| Coverage  | 2.88m <sup>2</sup> |
| Weight    | 26.784kg           |
| H x W x L | 1200x120x13.5 mm   |

| Dimensions    |         |
|---------------|---------|
| Thickness     | 13.5 mm |
| Width         | 120 mm  |
| Length        | 1200 mm |
| Top Layer     | 1.5 mm  |
| Backing Layer | 12 mm   |
| Bevel         | 1 mm    |

| Deviations             |                        |
|------------------------|------------------------|
| Deviation on thickness | ± 0.4 mm               |
| Deviation on width     | ± 0.4 mm               |
| Cup                    | ≤ 0.4 % of plank width |
| Bow                    | ≤ 0.7 % of length      |
| Spring                 | ≤ 0.7 % of length      |
| Height Difference      | ≤ 0.4 % of length      |

Installation




Glue down over concrete, plywood or wooden subfloor. Suitable for gluedown installation over radiant heating systems.

General Specifications

|           |                                                                                                                                                      |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use       | Residential, light commercial or commercial (Polyurethane Commercial)                                                                                |
| Accessory | <ul style="list-style-type: none"> <li>Round Stair nosings, Scotias, Skirting, Corners and Transition profiles</li> <li>Polyurethane glue</li> </ul> |
| Guarantee | Relative humidity must always be maintained                                                                                                          |

Storage & Usage



Air humidity 40% – 65%  
Temperature +18 ° – +22 ° C

Grade: Natural

| Description     |                                                               |
|-----------------|---------------------------------------------------------------|
| Surface Grade   | Natural                                                       |
| Plywood Grade   | WBP                                                           |
| Smooth Tight    | Unlimited                                                     |
| Holes           | Not Allowed                                                   |
| Bark Pockets    | Allowed Width 40mmx3mm 3 Pieces, No Cracking, Must be Filled. |
| Color Variation | Not Worst Natural Color Variation                             |
| Sound Knots     | No Limited, Could be crack knots.                             |
| Dead Knots      | Dead Knot Allow $\varnothing < 30\text{mm}$ , Must be Filled. |
| Pin Knots       | Allow 3 -5 pcs per board                                      |
| Ring Shake      | Not Allowed                                                   |
| Ends Crack      | Closed Crack Length 50mm Allowed.                             |
| Surface Crack   | Not Allowed                                                   |

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.