

Construction: Solid Wooden Flooring

Product Details

Product ID	100K70
Construction	Solid
Species (Top Layer)	Oak
Backing	—
Joint type	Tongue and Groove
Edges	Not Beveled
Pattern	Brick



Packaging

Pack

Quantity	21
Coverage	1.323m ²
Weight	15.876kg
H x W x L	700x90x16 mm

Dimensions

Thickness	16 mm
Width	90 mm
Length	700 mm
Tongue Width	5 mm
Groove Width	5 mm

Deviations

Deviation on thickness	± 1 mm
Deviation on width	± 1 mm
Cup	≤ 0.4 % of plank width
Bow	≤ 0.7 % of length
Spring	≤ 0.7 % of length
Height Difference	≤ 0.4 % of length

Installation




Glue down over concrete, plywood or wooden subfloor. Suitable for gluedown installation over radiant heating systems.

General Specifications

Use	Residential, light commercial or commercial (Polyurethane Commercial)
Accessory	• Round Stair nosings, Scotias, Skirting, Corners and Transition profiles • Polyurethane glue
Guarantee	Relative humidity must always be maintained

Storage & Usage



Air humidity 40% – 65%
Temperature +18 ° – +22 ° C

Grade: Natural

Description

Surface Grade	Natural	Sound Knots	No Limited, Could be crack knots.
Plywood Grade	—	Dead Knots	Dead Knot Allow $\varphi < 30\text{mm}$, Must be Filled.
Smooth Tight	Unlimited	Pin Knots	Allow 3 -5 pcs per board
Holes	Not Allowed	Ring Shake	Not Allowed
Bark Pockets	Allowed Width 40mmx3mm 3 Pieces, No Cracking, Must be Filled.	Ends Crack	Closed Crack Length 50mm Allowed.
Color Variation	Not Worst Natural Color Variation	Surface Crack	Not Allowed

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.