



Construction: 2-layer T&G Engineered Flooring

Product Details	
Product ID	204K1
Construction	Eng. Multi-Ply
Species (Top Layer)	Oak
Backing	Baltic Birch Wood
Joint type	Loose tongue and groove
Edges	4-sided bevel (4V)
Pattern	anel (Versailles), 4-Sided Beveled



Packaging	Pack
Quantity	6
Coverage	2.16m ²
Weight	26.784kg
H x W x L	600x600x18 mm

Dimensions	
Thickness	18 mm
Width	600 mm
Length	600 mm
Top Layer	3 mm
Backing Layer	15 mm
Bevel	1 mm

Deviations	
Deviation on thickness	± 0.4 mm
Deviation on width	± 0.4 mm
Cup	≤ 0.4 % of plank width
Bow	≤ 0.7 % of length
Spring	≤ 0.7 % of length
Height Difference	≤ 0.4 % of length

Installation




Glue down over concrete, plywood or wooden subfloor. Suitable for gluedown installation over radiant heating systems.

General Specifications

Use	Residential, light commercial or commercial (Polyurethane Commercial)
Accessory	• Round Stair nosings, Scotias, Skirting, Corners and Transition profiles • Polyurethane glue
Relative humidity must always be maintained	

Guarantee	• 5-year guarantee for residential applications • 2-year guarantee for light commercial applications
-----------	---

Storage & Usage



Air humidity 40% – 65%
Temperature +18 ° – +22 ° C

Finish: Polyurethane

Description	
Color	Walnut
Type	Polyurethane-Genc

Grade: Natural

Description	
Surface Grade	Natural
Plywood Grade	WBP
Smooth Tight	Unlimited
Holes	Not Allowed
Bark Pockets	Allowed Width 40mmx3mm 3 Pieces, No Cracking, Must be Filled.
Color Variation	Not Worst Natural Color Variation
Sound Knots	No Limited, Could be crack knots.
Dead Knots	Dead Knot Allow $\varphi < 30\text{mm}$, Must be Filled.
Pin Knots	Allow 3 -5 pcs per board
Ring Shake	Not Allowed
Ends Crack	Closed Crack Length 50mm Allowed.
Surface Crack	Not Allowed

Maintenance and Care

Regular maintenance; cleaning of dust and grit using a vacuum, followed by a thorough cleaning with recommended floor cleaners.

Floor surface areas that receive the most traffic and get worn down quicker, such as

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.