

Construction: 2-layer T&G Engineered Flooring

Product Details	
Product ID	207K220
Construction	Eng. Multi-Ply
Species (Top Layer)	Oak
Backing	Baltic Birch Wood
Joint type	Loose tongue and groove
Edges	4-sided bevel (4V)
Pattern	Brick



Packaging	Pack
Quantity	8
Coverage	2.816m ²
Weight	34.9184kg
H x W x L	2200x160x18 mm

Dimensions	
Thickness	18 mm
Width	160 mm
Length	2200 mm
Top Layer	3 mm
Backing Layer	15 mm
Bevel	1 mm

Deviations	
Deviation on thickness	± 0.4 mm
Deviation on width	± 0.4 mm
Cup	≤ 0.4 % of plank width
Bow	≤ 0.7 % of length
Spring	≤ 0.7 % of length
Height Difference	≤ 0.4 % of length

Installation




Glue down over concrete, plywood or wooden subfloor. Suitable for gluedown installation over radiant heating systems.

General Specifications	
Use	Residential, light commercial or commercial (Polyurethane Commercial)
Accessory	- Round Stair nosings, Scotias, Skirting, Corners and Transition profiles - Polyurethane glue
Relative humidity must always be maintained	

Guarantee	5-year guarantee for residential applications 2-year guarantee for light commercial applications
-----------	---

Storage & Usage



Air humidity 40% – 65%
Temperature +18 ° – +22 ° C

Finish: Polyurethane	Maintenance and Care
Description	Regular maintenance; cleaning of dust and grit using a vacuum, followed by a thorough cleaning with recommended floor cleaners.
Color	Dark Walnut
Type	Polyurethane-Genc
Grade: Country	Floor surface areas that receive the most traffic and get worn down quicker, such as

Description	
Surface Grade	Country
Plywood Grade	WBP
Smooth Tight	Unlimited
Holes	Not Allowed
Bark Pockets	Allowed Width 60mmx5mm 3 Pieces, No Cracking, Must be Filled.
Color Variation	All Color Variation
Sound Knots	Allowed Tight cracked
Dead Knots	Dead Knot Allow $\varphi < 80\text{mm}$, Must be Filled.
Pin Knots	No Limitation
Ring Shake	Not Allowed
Ends Crack	Closed Crack Length 100mm Allowed.
Surface Crack	Allowed

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.