

Construction: 2-layer T&G Engineered Flooring

| Product Details     |                         |
|---------------------|-------------------------|
| Product ID          | 208K78H                 |
| Construction        | Eng. Multi-Ply          |
| Species (Top Layer) | Oak                     |
| Backing             | Baltic Birch Wood       |
| Joint type          | Loose tongue and groove |
| Edges               | 4-sided bevel (4V)      |
| Pattern             | Herringbone             |



| Packaging |  | Pack         |
|-----------|--|--------------|
| Quantity  |  | 34           |
| Coverage  |  | 2.612288m2   |
| Weight    |  | 26.9065664kg |
| H x W x L |  | 784x98x15 mm |

| Dimensions    |        |
|---------------|--------|
| Thickness     | 15 mm  |
| Width         | 98 mm  |
| Length        | 784 mm |
| Top Layer     | 3 mm   |
| Backing Layer | 12 mm  |
| Bevel         | 1 mm   |

| Deviations             |                        |
|------------------------|------------------------|
| Deviation on thickness | ± 0.4 mm               |
| Deviation on width     | ± 0.4 mm               |
| Cup                    | ≤ 0.4 % of plank width |
| Bow                    | ≤ 0.7 % of length      |
| Spring                 | ≤ 0.7 % of length      |
| Height Difference      | ≤ 0.4 % of length      |

Installation




Glue down over concrete, plywood or wooden subfloor. Suitable for gluedown installation over radiant heating systems.

General Specifications

| Use       |                                                                                                                                                      |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use       | Residential, light commercial or commercial (Polyurethane Commercial)                                                                                |
| Accessory | <ul style="list-style-type: none"> <li>Round Stair nosings, Scotias, Skirting, Corners and Transition profiles</li> <li>Polyurethane glue</li> </ul> |
|           | Relative humidity must always be maintained                                                                                                          |

| Guarantee |                                                                                                                                                             |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <ul style="list-style-type: none"> <li>5-year guarantee for residential applications</li> <li>2-year guarantee for light commercial applications</li> </ul> |

Storage & Usage



Air humidity 40% – 65%  
Temperature +18 ° – +22 ° C

Finish: Polyurethane

| Description |                   |
|-------------|-------------------|
| Color       | Wenge             |
| Type        | Polyurethane-Genc |

Maintenance and Care

Regular maintenance; cleaning of dust and grit using a vacuum, followed by a thorough cleaning with recommended floor cleaners.

Floor surface areas that receive the most traffic and get worn down quicker, such as

Grade: Country

| Description     |                                                               |
|-----------------|---------------------------------------------------------------|
| Surface Grade   | Country                                                       |
| Plywood Grade   | WBP                                                           |
| Smooth Tight    | Unlimited                                                     |
| Holes           | Not Allowed                                                   |
| Bark Pockets    | Allowed Width 60mmx5mm 3 Pieces, No Cracking, Must be Filled. |
| Color Variation | All Color Variation                                           |
| Sound Knots     | Allowed Tight cracked                                         |
| Dead Knots      | Dead Knot Allow $\varphi < 80\text{mm}$ , Must be Filled.     |
| Pin Knots       | No Limitation                                                 |
| Ring Shake      | Not Allowed                                                   |
| Ends Crack      | Closed Crack Length 100mm Allowed.                            |
| Surface Crack   | Allowed                                                       |

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.