



Construction: 2-layer Engineered Wooden Profile

| Product Details     |                     |
|---------------------|---------------------|
| Product ID          | SKC100K14           |
| Construction        | Eng. Multi-Ply      |
| Species (Top Layer) | Oak                 |
| Backing             | Same as Top         |
| Joint type          | _____               |
| Edges               | Bottom Back Beveled |



| Packaging | Pack                |
|-----------|---------------------|
| Quantity  | 5                   |
| Coverage  | 11.75m <sup>2</sup> |
| Weight    | 41.125kg            |
| H x W x L | 2350x145x15 mm      |

| Dimensions    |         |
|---------------|---------|
| Thickness     | 15 mm   |
| Width         | 145 mm  |
| Length        | 2350 mm |
| Top Layer     | _____   |
| Backing Layer | _____   |
| Bevel         | _____   |

| Deviations             |        |
|------------------------|--------|
| Deviation on thickness | ± 1 mm |
| Deviation on width     | ± 1 mm |
|                        | _____  |
|                        | _____  |
|                        | _____  |


Installation



Glue on wall

| General Specifications |                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------|
| Use                    | Residential, light commercial or commercial                                                      |
| Accessory              | • Round Stair nosings, Scotias, Skirting, Corners and Transition profiles<br>• Polyurethane glue |
| Guarantee              | Relative humidity must always be maintained<br>• 5-year guarantee                                |

Storage & Usage



Air humidity 40% – 65%  
Temperature +18 ° – +22 ° C

Grade: Country

| Description     |                                                               |               |                                                               |
|-----------------|---------------------------------------------------------------|---------------|---------------------------------------------------------------|
| Surface Grade   | Country                                                       | Sound Knots   | Allowed Tight cracked                                         |
| Plywood Grade   | WBP                                                           | Dead Knots    | Dead Knot Allow $\varnothing < 80\text{mm}$ , Must be Filled. |
| Smooth Tight    | Unlimited                                                     | Pin Knots     | No Limitation                                                 |
| Holes           | Not Allowed                                                   | Ring Shake    | Not Allowed                                                   |
| Bark Pockets    | Allowed Width 60mmx5mm 3 Pieces, No Cracking, Must be Filled. | Ends Crack    | Closed Crack Length 100mm Allowed.                            |
| Color Variation | All Color Variation                                           | Surface Crack | Allowed                                                       |

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.