



Construction: 2-layer Engineered Wooden Profile

Product Details	
Product ID	SKR100K4
Construction	Eng. Multi-Ply
Species (Top Layer)	Oak
Backing	Same as Top
Joint type	
Edges	Bottom Back Beveled



Packaging	Pack
Quantity	10
Coverage	23.5m2
Weight	22.795kg
H x W x L	2350x40x15 mm

Dimensions	
Thickness	15 mm
Width	40 mm
Length	2350 mm
Top Layer	
Backing Layer	
Bevel	

Deviations	
Deviation on thickness	± 1 mm
Deviation on width	± 1 mm


Installation



Glue on wall

General Specifications	
Use	Residential, light commercial or commercial
Accessory	• Round Stair nosings, Scotias, Skirting, Corners and Transition profiles • Polyurethane glue
Guarantee	Relative humidity must always be maintained • 5-year guarantee

Storage & Usage



Air humidity 40% – 65%
Temperature +18 ° – +22 ° C

Grade: Country

Description			
Surface Grade	Country	Sound Knots	Allowed Tight cracked
Plywood Grade	WBP	Dead Knots	Dead Knot Allow $\varnothing < 80\text{mm}$, Must be Filled.
Smooth Tight	Unlimited	Pin Knots	No Limitation
Holes	Not Allowed	Ring Shake	Not Allowed
Bark Pockets	Allowed Width 60mmx5mm 3 Pieces, No Cracking, Must be Filled.	Ends Crack	Closed Crack Length 100mm Allowed.
Color Variation	All Color Variation	Surface Crack	Allowed

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.