



Construction: 2-layer Engineered Wooden Profile

Product Details	
Product ID	SKS301K26
Construction	Eng. Multi-Ply
Species (Top Layer)	Oak
Backing	Same as Top
Joint type	_____
Edges	Bottom Back Beveled



Packaging	Pack
Quantity	5
Coverage	11.75m ²
Weight	74.025kg
H x W x L	2350x260x15 mm

Dimensions	
Thickness	15 mm
Width	260 mm
Length	2350 mm
Top Layer	_____
Backing Layer	_____
Bevel	_____

Deviations	
Deviation on thickness	± 1 mm
Deviation on width	± 1 mm

Installation




Glue on wall

General Specifications

Use	Residential, light commercial or commercial
Accessory	• Round Stair nosings, Scotias, Skirting, Corners and Transition profiles • Polyurethane glue

Guarantee	Relative humidity must always be maintained • 5-year guarantee
-----------	---

Storage & Usage



Air humidity 40% – 65%
Temperature +18 ° – +22 ° C

Finish: Natural Oil

Description	
Color	Natural
Type	Natural Oil - Osmo

Maintenance and Care

Regular maintenance; cleaning of dust and grit using a vacuum, followed by a thorough cleaning with recommended floor cleaners.

Grade: Country

Description			
Surface Grade	Country	Sound Knots	Allowed Tight cracked
Plywood Grade	WBP	Dead Knots	Dead Knot Allow $\varphi < 80\text{mm}$, Must be Filled.
Smooth Tight	Unlimited	Pin Knots	No Limitation
Holes	Not Allowed	Ring Shake	Not Allowed
Bark Pockets	Allowed Width 60mmx5mm 3 Pieces, No Cracking, Must be Filled.	Ends Crack	Closed Crack Length 100mm Allowed.
Color Variation	All Color Variation	Surface Crack	Allowed

This technical data sheets was written by Ilex . All information contained in this data sheet was correct at the time of writing and publication. Ilex reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.